



VISUAL MAGNETICS GRAPHIC SYSTEM®

VM-POLYEDGE™ UV

Visual Magnetics® VM-POLYEDGE™ UV is a value price point, 11-mil* magnetic receptive white polypropylene film with a matte print surface. VM-POLYEDGE UV is ideal for producing matte, high resolution photo and artwork reproductions and high value POP signage using analog and digital printing technologies. VM-POLYEDGE UV features a patented Micro-Iron® back-coating enabling displays to be effortlessly updated, easily installed, layered, transported, stored or recycled and keeps graphics surfaces clean with zero mark-off.

Roll-Out



Features and Benefits

- Value Price Point.
- Unlimited Shelf Life.
- PVC free.
- Premium matte print coating optimized for analog and digital print devices.
- Polypropylene base.
- Water / Smudge resistant print surface – Easy to clean.
- 100% opaque – No show through.
- Easy to install – No frames, wraps or stretching necessary.

Application Information

- Excellent for durable displays and POP signage.
- Apply, remove and store like any other MagnaMedia.
- Polypropylene base not designed for high temperature applications.

Physical Data

Total Caliper*	11-mil / 279 Micron	Opacity	100%
Gloss	Matte	Fire Rating	Class B (ASTME-84-98)
Whiteness*	Testing in progress	Optimal Conditions	50% RH / 70°F

Products / Sizes


PRODUCT CODE	AVAILABLE SIZES	
VMPEUV-54100	54 in x 100 ft – 3 in core	(137.2 cm x 30.5 m)
VMPEUV-54300A	54 in x 300 ft – 3 in core	(137.2 cm x 91.4 m)
VMPEUV-54300B	54 in x 300 ft – 6 in core	(137.2 cm x 91.4 m)
VMPEUV-60100	60 in x 100 ft – 3 in core	(152.4 cm x 30.5 m)
VMPEUV-60300A	60 in x 300 ft – 3 in core	(152.4 cm x 91.4 m)
VMPEUV-60300B	60 in x 300 ft – 6 in core	(152.4 cm x 91.4 m)

* Thickness and whiteness listed is nominal.

VM-POLYEDGE™ UV (Continued)

Printer Compatibility

VM-POLYEDGE UV is compatible with most UV, analog and digital printing technologies (see chart).



Recyclability

All MagnaMedia, including VM-POLYEDGE UV, will be recycled into energy and new steel production when returned to Visual Magnetics per our "Recycling Retired Graphics" program available for download at www.visualmagnetics.com.

Protecting Images

Liquid laminates are recommended as they can be easily applied to the textured surface with good results. Apply minimally to maintain surface texture. Always pretest liquid laminates for compatibility prior to applying to finished graphic.

COMPATIBILITY KEY

- VM certified best results
- Uncertified – Profile dependent
- ✗ Not compatible
- △ HP Certified for Latex Inks

Renew



Visual Magnetics
Limited Partnership
1 Emerson Street,
Mendon, MA 01756
P 508 381-2400
F 508 381-2401
Toll Free 855 VISMAG4

VisualMagnetics.com
info@visualmagnetics.com

The information presented in this product data sheet is based upon Visual Magnetics' present knowledge of the product and is believed to be accurate. Products often are improved which may cause the current information presented to be out of date. It is always the users responsibility to determine suitability of this product for the intended application prior to production.