

VISUAL MAGNETICS GRAPHIC SYSTEM

VM-POLYeight®UV

Visual Magnetics® VM-POLYeight UV is a 12-mil*, magnetic receptive white polyester film with a high gloss print surface. VM-POLYeight UV is ideal for producing high resolution photo and artwork reproductions, overlays, and economical POP signage using most digital and analog printing technologies and features a patented Micro-Iron® back-coating enabling displays to be effortlessly updated, easily installed, layered, transported, stored or recycled.

Roll-Out



Features and Benefits

- Premium gloss print coating optimized for analog and UV-Cured print devices.
- 12-mil* polyester base. Economical with quality "hand."
- Water/smudge resistant print surface.
- 100% opaque No show through.
- · Easy to install No frames, wraps or stretching necessary.
- PVC free.

Application Information

- Excellent for durable displays and POP signage.
- · Apply, remove and store like any other MagnaMedia.
- Polyester base designed for high temperature applications.

Physical Data

Total Caliper* 12-mil / 305 Micron Opacity 100%

Gloss Gloss Fire Rating Class A (ASTME-84-98)

Whiteness* 100% Optimal Conditions 50% RH / 70°F

Products / Sizes

PRODUCT CODE	AVAILABLE SIZES		
VMP8UV-54100	54 in x 100 ft – 3 in core	(137.2 cm x 30.5 m)	
VMP8UV-60100	60 in x 100 ft – 3 in core	(152.4 cm x 30.5 m)	

* Thickness and whiteness listed is nominal.

VM-POLYeight®UV (Continued)

Printer Compatibility


VM-POLYeight UV is compatible with most UV-Cured and analog printing technologies (see chart).

COMPATIBILITY KEY

- VM certified best results
- Uncertified Profile dependent
- X Not compatible
- △ HP Certified for Latex Inks







Recyclability

All MagnaMedia, including **VM-POLYeight UV**, will be recycled into energy and new steel production when returned to Visual Magnetics per our "Recycling Retired Graphics" program available for download at www.visualmagnetics.com.

Protecting Images

Liquid laminates are recommended as they can be easily applied to the textured surface with good results. Apply minimally to maintain surface texture. Always pretest liquid laminates for compatibility prior to applying to finished graphic.

Visual Magnetics Limited Partnership 1 Emerson Street, Mendon, MA 01756 P 508 381-2400 F 508 381-2401 Toll Free 855 VISMAG4

Visual Magnetics.com info@visual magnetics.com

The information presented in this product data sheet is based upon Visual Magnetics' present knowledge of the product and is believed to be accurate. Products often are improved which may cause the current information presented to be out of date. It is always the users responsibility to determine suitability of this product for the intended application prior to production.