

Material Safety Data Sheet – 16 Sections

Date of Preparation: July 30, 2015

SECTION 1—CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ActiveWall® Commercial Grade Micro-Iron® Latex Primer

PRODUCT CLASS: Compounded water base paint.

Visual Magnetics Limited Partnership

1 Emerson St

Mendon, MA 01756

Phone: 508-381-2400

SECTION 2— COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	Prod. Cas#	% by weight	OSHA PEL/TWA	ACGIH TLV/STEL
Propylene Glycol.	57-55-6	<1.0	10 mg/m3	N/A

SECTION 3— HAZARDS IDENTIFICATION

Propylene Glycol is hazardous if ingested, and slightly hazardous in case of eye or skin contact, and if inhaled.

SECTION 4—FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin: Wash with soap and water. If rash develops, seek medical attention.

Eyes: Flush with water. Seek medical attention if irritation persists.

Inhalation: Remove to fresh air. Seek medical attention if symptoms persist.

Ingestion: Drink water. Seek medical attention if symptoms persist.

SECTION 5—FIRE-FIGHTING MEASURES

Not Flammable

Extinguishing Media: Water, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedure: Wear full protective clothing and self-contained breathing apparatus.

Flash Point..... N/A

Flammable Limits..... N/A

Auto-Ignition Temp..... N/A

Unusual Fire and Explosion Hazards: Sealed container may rupture, keep cool with water.

SECTION 6—ACCIDENTAL RELEASE MEASURES

Leak and Spill Procedures - In case of spill: Wear protective clothing when cleaning up spills. Ventilate area. Spill area will be slippery. Contain spill. Recover as much as possible for reuse. Spread commercial absorbent over remainder and place into sealed containers for disposal.

SECTION 7—HANDLING AND STORAGE

Protect from freezing. Store in cool, ventilated area. Use rubber gloves and splash-proof goggles when transferring contents. For confined, poorly ventilated areas, use vapor cartridge breathing apparatus.

SECTION 8—EXPOSURE CONTROL / PERSONAL PROTECTION

Exposure limits: No data available.

Personal Protection—Respiratory: For confined areas with poor ventilation, use vapor cartridge breathing apparatus.

Hands/skin: Use rubber gloves.

Eyes: Splash-proof chemical goggles.

SECTION 9—PHYSICAL AND CHEMICAL PROPERTIES

Physical State.....	Liquid
Boiling Point.....	212°F
Vapor Density.....	As Water
Vapor Pressure.....	As Water
Solubility in H ₂ O.....	Miscible
Appearance/Odor.....	Black color with mild odor.
Specific Gravity.....	2.46
VOC.....	18.6 grams/liter
pH.....	8.0—9.0
Freeze Point.....	32°F
Decomposition Temp.....	>32°F
Viscosity.....	16K—19K cps.
Flash Point.....	N/A
Flammable Limits.....	N/A
Auto-Ignition Temp.....	N/A

SECTION 10—STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Will not occur.

Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.

Incompatibility (Materials to Avoid): Strong oxidizing agents.

SECTION 11—TOXICOLOGICAL INFORMATION

No information or data specific to the product on toxicological effect is available.

SECTION 12—ECOLOGICAL INFORMATION

No data available.

SECTION 13—DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Most states prohibit disposal of liquids in landfills.

SECTION 14—TRANSPORT INFORMATION

DOT—Not regulated.

SECTION 15—REGULATORY INFORMATION

TSCA—All ingredients in the product are listed on the TSCA inventory.

CERCLA—This material contains a trace amount of an ingredient that is regulated under CERCLA 40 CFR 302.4.

SECTION 16—OTHER INFORMATION

Product Hazard Rating: Health—1, Flammability—0, Reactivity—0, Personal Protection--B
